

PE-PHOTOPAPER

H62210 UltraWhite Alpine 240 g/m² satin

Product Specification*

| | | | | |
|------------------------|------------------|------|---|-----|
| Thickness | µm | 240 | ± | 6 |
| Weight | g/m ² | 248 | ± | 7 |
| Gloss (BYK) 60° | % | 17 | ± | 5 |
| Colour MLD UVO | L | 94,2 | ± | 0,5 |
| | a | -0,4 | ± | 0,3 |
| | b | -2,4 | ± | 0,5 |
| | delta b | 10,8 | ± | 0,8 |

| | |
|----------------------------------|-----|
| CIE Whiteness (D65 / 10°) | 145 |
|----------------------------------|-----|

| | |
|----------------|------|
| Opacity | > 90 |
|----------------|------|

| | |
|---------------------|------------|
| Laminability | Hot & Cold |
|---------------------|------------|

| | |
|----------------|--|
| Formats | A4, A3, A3+ Box à 50 sheets A4, A3, A3+ Bulk à 500 sheets |
|----------------|--|

| | | |
|--------------|----------------|---------------------------------|
| Rolls | <i>width</i> | 17, 24, 36, 42, 50, 54, 60 inch |
| | <i>lengths</i> | 30 m standard |

Applications

Large format printing like POS-Signage, Posters, Exhibition graphics

Benefits & Properties

Outstanding media colour consistency, large colour gamut, excellent image sharpness, smear-resistant, very consistent layflat, instant dry, universal compatibility

Compatible Printers

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

For best print results we recommend our ICC profiles to be downloaded from our website.

Directions for use

Store material only in original boxes, out of direct sunlight under normal climatic conditions (23°, 50% RH).
You can improve results by using the best possible printer settings

**All possible modifications are reserved*