

SIGNOLIT® SI 134 Semi-Matte 215g Polypropylene Roll-Up Film

Description	<i>Material</i>	- highly white polypropylene film
	<i>Coating</i>	- microporous coating
	<i>Properties</i>	- good scratch-resistance - lamination right to the edges - reduced reflections on the printed surface - brilliant colour reproduction
	<i>Application</i>	- indoor
	<i>Printing Systems</i>	- bubblejet and piezo
	<i>Inks</i>	- water-based dye and pigmented, latex
Examples of use	<i>Indoor</i>	- posters, POS, roll-up displays, exhibition panels
Laminating	It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate. If dye inks are used, SI 134 must be laminated indoor and outdoor to improve light-fastness and smudge-proofness. We recommend to use self-adhesive PP laminating foils for cold lamination.	
Technical data	<i>Base material</i>	white opaque polypropylene film
	<i>Thickness</i>	~ 230 µm
	<i>Grammage</i>	~ 215 g/m ²
	<i>Opacity</i>	~ 0,71
	<i>Core</i>	76mm Ø
	<i>Dimensions</i>	914 mm x 40 m 1067 mm x 40 m 1270 mm x 40 m
Storage	After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.	
Disposal	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.	



Digit Bt.
1125 Budapest, Istenehegyi út 29. Phone: +36 1 2245456
Email: info@digit.hu Web: www.nagyformatumu.hu Webshop: www.digitdisplay.eu